

## Laser Perforation for Tipping Paper



*Picture shows the turnkey, ready for production MLP-50 TWIN system including two Micro Perforators, the Rewinder with slitting knives and 0- meter option, both CO<sub>2</sub> - Laser Sources and the control cabinet.*

The MLP-50 TWIN System is a turnkey Laser Perforator Systems which offers highly attractive state-of-the-art technology for offline perforation of cigarette tipping paper.

The MLP-50 TWIN System perforates a maximum of 32 rows and up to 1.000.000 holes/second at a maximum web speed of 700 m/min. The typical web width is 270 mm for multiple bobbin operation.

The MLP-50 TWIN System is a ready for production system which perforates an extremely consistent hole-to-hole quality which results into a minimum standard deviation giving the MLP-50 TWIN System the highest reliability.

## Technical details of the MLP-50 TWIN System:

### Rewinder:

- Max. bobbin diameter: 800 mm
- Paper length unwind: max. 4000 m, optional up to 12000m
- Max. bobbin / paper width: 270 mm, other width on request
- Ramp up time: 0 - 700 m/min below 3 sec.
- Max. winding speed: 700 m/min
- Printed and un-printed paper: 35 to 45 gr. / sqm.
- Web guide: 2 optical edge sensor for best winding quality
- Slitter: max. 4 knives for inline slitting
- Base plate: solid steel base plate for perfect long term stability

### Micro Perforator:

- Based on MLT patented multiple Vario-Polygon System
- Rotating speed: up to 70.000 RPM per polygon
- Max. optical pulse frequency: up to 1.000.000 holes / sec, 31.250 Hz per row
- Hole density: range from 5 - 50 holes/cm
- Typ. Porosity: 50 to over 4000 Coresta Units
- Hole diameter: adjustable from 50 -300 µm

### Focusing Heads:

- Max. 32 perforation heads
- All heads can be moved across the whole web
- Each focusing lens is adjustable with 0,01 mm resolution
- Each head with individual shutter

### CO<sub>2</sub> – Laser source with 10,6 µm wavelength:

- Laser power ranging from 2000 Watt to 8000 Watt
- Optimised power stabilisation

### Chiller:

- Water-to-Air or Water-to-Water cooling
- +/- 1°C temperature regulation

### Exhaust dust Filter system:

- Various models are available, suitable to the demand
- Removes and filters debris of the perforation process